



# DL300

## Dump Controller & Load

APRS World, LLC specializes in data logging and control equipment primarily for the renewable energy industry. To learn more about this product or any of our other products, please visit us online at:

[www.aprsworld.com](http://www.aprsworld.com)

APRS World's **DL300 Series Dump Controller and Load** is an integrated solution designed to prevent 12 or 24 volt batteries from overcharging. It is designed to be used with small wind, solar, or hydro systems. The **DL300** is compact and easy to install. It incorporates a 300 watt resistor / heater and controller board in a stout 18 gauge powder coated steel enclosure.



### Specifications:

#### Operation

- PWM (Pulse Width Modulation) for highest charging performance without flicker
- Selectable three stage charging or over voltage protection mode
- Selectable for sealed or flooded batteries using jumper
- Status and fault indicator LEDs

#### Connections

- #10-32 brass screws for V+ and V-
- Two 1/2" / 3/4" concentric NPT knockouts and two 1/2" NPT knockouts

#### Mounting

- Mounts to vertical concrete, metal, drywall, or other non-flammable surface.
- Uses four #10 screws
- Body sits 19mm out from wall
- NEMA 1 enclosure for indoor mounting

#### Weight and Dimensions

- Dimensions: 88mm wide, 95mm tall, 470mm long (3.375 x 3.75 x 18.5 in)
- Weight: 1.94 kg (4.28 pounds)
- Shipping Dimensions: 102 mm wide, 108 mm tall, 508 mm long (4.0 x 4.25 x 20 in)
- Shipping Weight: 2.15 kg (4.75 pounds)

#### Materials

- Enclosure: 18 gauge mild steel, powder coated black
- Circuit board: FR-4, 1.6mm (0.062 in), double sided, plated through holes, solder mask, silk screen, gold plating
- Hardware: stainless steel, zinc plated steel, aluminum, and Nylon
- Shipping carton: corrugated cardboard

#### Power, 12 volt version, DL300-12

- Operating voltage range: 7 to 32 volts DC
- Recommend fuse or circuit breaker: 30 amps
- Integrated load resistor: 0.75 ohm, 300 watt, wire wound
- Quiescent current when not load dumping: 2.6mA @ 12 volts

#### Power, 24 volt version, DL300-24

- Operating voltage range: 7 to 32 volts DC
- Recommend fuse or circuit breaker: 15 amps
- Integrated load resistor: 3 ohms, 300 watt, wire wound
- Quiescent current when not load dumping: 3.0mA @ 24 volts

Voltage Set Points			
Type	Mode	12V	24V
Flooded	Bulk	14.6	29.2
	Float	13.4	26.8
	Protect	16.0	32.0
Sealed	Bulk	14.3	28.6
	Float	13.4	26.8
	Protect	15.0	30.0

### DL300 - Dump Controller & Load

DL300-12 Part Number: APRS8400

DL300-24 Part Number: APRS8401

Shipping Weight: ≤ 2.15 kg / 4.75 lb

RoHS: compliant



Winona, Minnesota

+1-507-454-2727

info@aprsworld.com